

**LEADMATE PATINATION OIL**

Colour	Product Code	Pack Size	Box Qty
Grey	PATOIL05	500ml	10
	PATOIL1	1Ltr	10

**Product Description**

Lead Mate Patination Oil has been specially formulated to provide a protective coating for newly installed leadwork that helps to prevent the white carbonate staining that affects new lead and surrounding tiles, brickwork, stonework etc.

Just one coat of Patination Oil also helps to provide uniform, attractive appearance to newly installed lead and helps the ageing process whilst the natural patina of the lead is being formed.

It is particularly important to treat areas of newly installed lead that are subject to water flowing over the surface onto surrounding areas as staining of tile and brick will be more severe in such circumstances.

**Benefits**

- Works on all newly fixed lead work.
- Prevent unsightly staining.
- Improves initial appearance and assists in natural ageing of lead.
- Recommended by the Lead Sheet Association.

**Limitations**

- Do not allow patination oil to come into contact with Bitumen or Polycarbonate sheets.
- Always test a small inconspicuous area prior to full application.
- As the company cannot be aware of all the applications and materials its product may be used on, it is the user's responsibility to determine suitability for use. Please contact Technical Services for advice or request Technical Data Sheet.

**Application**

- See side panel for tips on dispensing from this unique no spill pack.
- Always wear gloves and only apply in a well ventilated area.
- Shake can well before use.
- Surfaces must be totally dry before application.
- Apply oil evenly using a soft absorbent cloth, work horizontally starting at the top and maintain a wet edge at all times.
- DO NOT APPLY IN A CIRCULAR MOTION AS THIS WILL LEAVE AN IMPRESSION ON THE LEAD.
- Only one coat is required.

- Before clipping apply to underside of lead to approx 50mm from the edge.
- Apply to all areas, including clips and trim, and coat between laps.
- VERY IMPORTANT – Always apply as soon as possible after installation, or at the end of each working day, or if rain is expected apply before rain.

#### Coverage

Approximately 55-65 square metres of lead can be treated by a litre of Patination Oil.

#### Specific Data

Appearance	Brown/Yellow liquid
Boiling Point	152°C
Flash Point	38°C
SG @ 20°C	0.78
Working Temperature	5 to 40°C

#### Health & Safety

Consult MSDS for full list of hazards.

#### Storage

Store in cool, dry conditions between +5 and +30°C. Ensure good ventilation. Storage outside these parameters will dramatically reduce shelf life.

#### Shelf Life

12 months from date of manufacture when stored as directed.

*The technical data contained herein is based on our present knowledge and experience and we cannot be held liable for any errors, inaccuracies, omissions or editorial failings that result from technological changes or research between the date of issue of this document and the date the product is acquired. Before using the product, the user should carry out any necessary tests in order to ensure that the product is suitable for the intended application. Moreover, all users should contact the seller or the manufacturer of the product for additional technical information concerning its use if they think that the information in their possession needs to be clarified in any way, whether for normal use or a specific application of our product. Our guarantee applies within the context of the statutory regulations and provisions in force, current professional standards and in accordance with the stipulations set out in our general sales conditions. The information detailed in the present technical data sheet is given by way of indication and is not exhaustive. The same applies to any information provided verbally by telephone to any prospective or existing customer.*